





TR-35 is premium ribbon for wash care ribbon application having a wide range of print adaptability on satin as well as nylon. It is known for its low printing temperature, high blackness and superior media adaptability. It has a high performance on both the high-density washing label and the sparsely woven ribbon. The low printing temperature and blackness.

Sensitivity

– Printing speed



– Printing temperature



Resistance Test

– Washing resistance test

With a printed label in a washing machine with 4% soap water at 40°C for 30 minutes, observe the print attenuation



– Dry-cleaning resistance test

With a printed label in a washing machine with CCL4 solution at 40°C for 30 minutes, observe its print attenuation




– Ironing test

With a printed label under a steam ironing machine for 5 minutes, observe its print attenuation




Printing Quality


Darkness




0° barcode




90° barcode




Sharpness



Min. printable character



Graphics



Wash Care Labels

Recommended Wash care grades

- 
 Nylon Taffeta
- 
 Polyester Taffeta
- 
 Polyester Satin
- 
 Acetate Satin





Properties

PET film

Thickness: 4.5 µm

Ribbon

Thickness: 6.0±0.3µm

Ink

Color: Black Melting point: 105±3°C

Storage Condition

Temperature: 5-35°C Humidity: 20-80%
Validity period: 12 months

CERTIFICATION



Recommended Applications

Fixed Asset



Pharmaceutical



Nursery Gardens & Flowers



Daily Chemicals



Electrical equipment



Mechanical Equipment




Chemical Industry



Steel & Iron Manufacturing



Digital & Electronic Labels



Clothing Tags



Logistic



Food & Beverage



Production Lines



Automobile Industry



Warehouse



Retails Label



Wooden Products



Flexible Packaging

