




R-303, as a high-performance, cost-effective resin ribbon.


With high printing blackness, excellent media adaptability and alcohol resistance. It is widely used in electrical appliances, equipment, electronics and other industries and received wide acclaim.

Sensitivity

– Printing speed



– Printing temperature



Resistance Test

– Resistance test

Slight exposure begins after approx. **X** cycles with a 700GM weight load

Smudge resistance



Scratch resistance



Alcohol



95% Industrial alcohol

Gasoline



92 # Gasoline

Braking fluid



Bosch dot4 plus

– Water resistance test

100




– Low-temperature test

100°C




Printing Quality


Darkness




0° barcode




90° barcode




Sharpness



Min. printable character



Graphics



Substrate Compatibility

Recommended substrate grades

Uncoated Paper
Writing paper, vellum
...

Coated Paper
Art paper, art printing paper, high gloss paper
...

Synthetic Paper
Synthetic paper

Film labels
PP, PET, PE, BOPP, PVC
...



Properties

PET film

Thickness: 4.5 µm

Ribbon

Thickness: 7.7±0.3µm

Ink

Color: Black Melting point: 105±3°C

Storage Condition

Temperature: 5-35°C Humidity: 20-80%
Validity period: 12 months

CERTIFICATION



ISEGA



Recommended Applications

Fixed Asset



Pharmaceutical



Nursery Gardens & Flowers



Daily Chemicals



Electrical equipment



Mechanical Equipment




Chemical Industry



Steel & Iron Manufacturing



Digital & Electronic Labels



Clothing Tags



Logistic



Food & Beverage



Production Lines



Automobile Industry



Warehouse



Retails Label



Wooden Products



Flexible Packaging

