





XPR TTO Premium Resin is the enhanced tto premium resin ribbon, with good resistance to smudge and scratch, excellent printing quality, sensitivity and good resistance to high temperature

Sensitivity

– Printing speed



– Printing temperature



Resistance Test

– Resistance test

Slight exposure begins after approx. **X** cycles with a 700GM weight load

Smudge resistance



Scratch resistance



Alcohol



95% Industrial alcohol

Gasoline



92 # Gasoline

Braking fluid



Bosch dot4 plus

– Water resistance test

100




– Low-temperature test

180°C




Printing Quality


Darkness




0° barcode



90° barcode




Sharpness



Min. printable character



Graphics



Substrate Compatibility

Recommended substrate grades

Uncoated Paper Writing paper, vellum ...	Coated Paper Art paper, art printing paper, high gloss paper ...	Synthetic Paper Synthetic paper	Film labels PP, PET, PE, BOPP, PVC ...
--	--	------------------------------------	--





Properties

PET film

Thickness: 4.5 µm

Ribbon

Thickness: 9.0±0.3µm

Ink

Color: Black Melting point: 80±3°C

Storage Condition

Temperature: 5-35°C Humidity: 20-80%
Validity period: 12 months

CERTIFICATION



Recommended Applications

Fixed Asset



Pharmaceutical



Nursery Gardens & Flowers



Daily Chemicals



Electrical equipment



Mechanical Equipment



Chemical Industry



Steel & Iron Manufacturing



Digital & Electronic Labels



Clothing Tags



Logistic



Food & Beverage



Production Lines



Automobile Industry



Warehouse



Retails Label



Wooden Products



Flexible Packaging

